

## **Autoclave Innovation**

## Exhaust Steam-Free Autoclave with Deodorizing





ISO 13485 CERTIFIED Products shown in this brochure are manufactured by the company, ISO 13485 certified. STERILIZING SIMPLY AND WELL

**HIRAYAMA** 






Main specifications		
Model	HVN-50	HVN-85
Outer dimensions (mm)	W547 x D552 x H1050 mm	W669 x D680 x H1011 mm
Chamber size (Effective capacity)	φ 300 x D710 mm (50 liter)	φ 420 x D615 mm (85 liter)
Power source	AC220V, 50/60Hz, Single-phase	
Power consumption	2.0KW (10A)	3.0KW (15A)
Net weight (approx.)	73kg	88kg
Chamber material	Stainless Steel (SUS304)	
Sterilization temperatue range	105°C or 135°C variable	
Maximum allowable pressure (Gauge pressure)	0.255MPa	
Temperature display range	5 ∼137°C	
Sterilization timer	1 ~ 250 minutes	
Deodorizing timer	1 ~ 90 minutes	
Selective mode	Waste material sterilization: Heating ⇒ Sterilization ⇒ Deodorizing Liquid sterilization: Heating ⇒ Sterilization ⇒ Forced cooling (Hi) Liquid sterilization: Heating ⇒ Sterilization ⇒ Natural cooling (Low)	
Exhaust bottle (filled)	3.4 liter, built-in	
Pressure gauge	Analog display, 0 ~ 0.4MPa	
Safety devices/ Warning alarm	Pressure safety valve, Circuit breaker, Lack-of-water prevention switch	
	Error indication (Exhaust clogging, Lack-of-water, Temperature sensor wire breakage, Over temperature, Over cooling, Open/close lever locking failure)	
Accessories	SS Wire basket (2pcs), Heater cover, Drain hose, Exhaust hose, Drain bottle, Castor stopper (2pcs)	

## **Optional accessoriess**







Stainless Steel Wire Basket  $\phi$  270 × H270mm  $\phi$  380 × H285mm



Stainless Steel Busket φ 390 × H285mm



Wasting Bag A. 500 × 700mm (200pcs) B. 620 × 820mm (200pcs)

Specifications and appearance are subject to change without notice due to continuous product improvement.



http://www.hirayama.com.cn/

Manufacturing Corp.